

# VRAM Transfer Manager

Version 1.0.0

**The contents in this document are highly  
confidential and should be handled accordingly.**

**Confidential**

These coded instructions, statements, and computer programs contain proprietary information of Nintendo of America Inc. and/or Nintendo Company Ltd. and are protected by Federal copyright law. They may not be disclosed to third parties or copied or duplicated in any form, in whole or in part, without the prior written consent of Nintendo.

---

## Table of Contents

---

1	Introduction .....	5
2	VRAM Transfer Manager.....	6
2.1	Overview .....	6
2.2	Initializing the VRAM Transfer Manager.....	6
2.3	Registering a VRAM Transfer Task .....	7
2.4	Executing a VRAM Transfer Task.....	8
2.5	Obtaining the Size of the VRAM Transfer Tasks .....	8

---

## Code

---

Code 2-1 Initializing the VRAM Manager .....	7
--	---

---

## Tables

---

Table 2-1 Data Transfer Destination Types .....	7
---	---

---

## Figures

---

Figure 2-1 Sketch of the VRAM Manager .....	6
---	---

## Revision History

Version	Revision Date	Description
1.0.0	01/05/2005	Changed an instance of "NITRO" to "Nintendo DS."
0.1.0	07/16/2004	Initial version.

# 1 Introduction

The Nintendo DS does not allow the contents of VRAM to be rewritten during a screen display period. To rewrite VRAM contents while displaying a screen with an application, the application should normally be programmed to write data to the VRAM during V-Blank periods. The VRAM transfer manager in the NITRO-System library provides a feature that holds VRAM rewrite requests from applications in queue so the requested data can be written to VRAM during a V-Blank period.

## 2 VRAM Transfer Manager

### 2.1 Overview

The VRAM transfer manager provides features that register user requests to rewrite VRAM to the queue as VRAM transfer tasks, and at a later time write the data to the VRAM according to the registered tasks. These features are used to write data to VRAM during a V-Blank period according to VRAM transfer tasks registered during a screen display period.




Figure 2-1 Diagram of the VRAM Manager

### 2.2 Initializing the VRAM Transfer Manager

Before using the VRAM transfer manager, it must be initialized. Call the following function to initialize the VRAM transfer manager.

```
void NNS_GfdInitVramTransferManager(
    NNSGfdVramTransferTask* pTaskArray, u32 lengthOfArray);
```

The `NNS_GfdInitVramTransferManager()` function initializes the VRAM transfer manager and sets it to an available state.

The VRAM transfer manager saves VRAM transfer tasks in an array of `NNSGfdVramTransferTask` structure. When initializing the VRAM transfer manager, the user needs to prepare the `NNSGfdVramTransferTask` structure array. The user needs to set a pointer to the array to the first argument `pTaskArray` of the `NNS_GfdInitVramTransferManager()` function and the size of the array to the second argument `lengthOfArray`.

16 bytes are required to register one VRAM transfer task. Prepare the size of the `NNSGfdVramTransferTask` structure array to match the maximum number of VRAM transfer tasks to register to the VRAM transfer manager at once.

**Code 2-1 Initializing the VRAM Manager**

```
#define NUM_TASKS    8

NNSGfdVramTransferTask    taskArray[NUM_TASKS];

NNS_GfdInitVramTransferManager(taskArray, NUM_TASKS);
....
```

**2.3 Registering a VRAM Transfer Task**

Call the following function to register a VRAM transfer task to the VRAM transfer manager.

```
BOOL NNS_GfdRegisterNewVramTransferTask(
    NNS_GFD_DST_TYPE type, u32 dstAddr, void* pSrc, u32 szByte);
```

The `NNS_GfdRegisterNewVramTransferTask()` function sequentially registers specified VRAM rewrite data to the VRAM transfer manager queue as a VRAM transfer task. The number of VRAM transfer tasks that can be registered to the VRAM transfer manager at once is the number of elements in the `NNSGfdVramTransferTask` structure array specified when initializing the VRAM transfer manager.

For the `type` argument of the data transfer destination type, specify what type of data to transfer according to the VRAM transfer manager. The following types can be specified for `type`.

**Table 2-1 Data Transfer Destination Types**

Category	Constants Indicating the Data Transfer Destination Type	Meaning
3D	<code>NNS_GFD_DST_3D_TEX_VRAM</code>	3D texture image rewrite
	<code>NNS_GFD_DST_3D_TEX_PLTT</code>	3D texture palette rewrite
	<code>NNS_GFD_DST_3D_CLRIMG_COLOR</code>	3D clear image color rewrite
	<code>NNS_GFD_DST_3D_CLRIMG_DEPTH</code>	3D clear image depth rewrite
2D main	<code>NNS_GFD_DST_2D_background0_CHAR_MAIN</code>	2D main BG0 character rewrite
	<code>NNS_GFD_DST_2D_background1_CHAR_MAIN</code>	2D main BG1 character rewrite
	<code>NNS_GFD_DST_2D_background2_CHAR_MAIN</code>	2D main BG2 character rewrite
	<code>NNS_GFD_DST_2D_background3_CHAR_MAIN</code>	2D main BG3 character rewrite
	<code>NNS_GFD_DST_2D_background0_SCR_MAIN</code>	2D main BG0 screen rewrite
	<code>NNS_GFD_DST_2D_background1_SCR_MAIN</code>	2D main BG1 screen rewrite
	<code>NNS_GFD_DST_2D_background2_SCR_MAIN</code>	2D main BG2 screen rewrite
	<code>NNS_GFD_DST_2D_background3_SCR_MAIN</code>	2D main BG3 screen rewrite
	<code>NNS_GFD_DST_2D_background2_BMP_MAIN</code>	2D main BG2 bitmap rewrite
	<code>NNS_GFD_DST_2D_background3_BMP_MAIN</code>	2D main BG3 bitmap rewrite
	<code>NNS_GFD_DST_2D_OBJECT_PLTT_MAIN</code>	2D main OBJ palette rewrite
	<code>NNS_GFD_DST_2D_background_PLTT_MAIN</code>	2D main BG palette rewrite
	<code>NNS_GFD_DST_2D_OBJECT_EXTPLTT_MAIN</code>	2D main OBJ extended palette rewrite
	<code>NNS_GFD_DST_2D_background_EXTPLTT_MAIN</code>	2D main BG extended palette rewrite
	<code>NNS_GFD_DST_2D_OBJECT_OAM_MAIN</code>	2D main OAM rewrite
	<code>NNS_GFD_DST_2D_OBJECT_CHAR_MAIN</code>	2D main OBJ character rewrite

Category	Constants Indicating the Data Transfer Destination Type	Meaning
2D sub	NNS_GFD_DST_2D_background0_CHAR_SUB	2d sub BG0 character rewrite
	NNS_GFD_DST_2D_background1_CHAR_SUB	2d sub BG1 character rewrite
	NNS_GFD_DST_2D_background2_CHAR_SUB	2d sub BG2 character rewrite
	NNS_GFD_DST_2D_background3_CHAR_SUB	2d sub BG3 character rewrite
	NNS_GFD_DST_2D_background0_SCR_SUB	2d sub BG0 screen rewrite
	NNS_GFD_DST_2D_background1_SCR_SUB	2d sub BG1 screen rewrite
	NNS_GFD_DST_2D_background2_SCR_SUB	2d sub BG2 screen rewrite
	NNS_GFD_DST_2D_background3_SCR_SUB	2d sub BG3 screen rewrite
	NNS_GFD_DST_2D_background2_BMP_SUB	2d sub BG2 bitmap rewrite
	NNS_GFD_DST_2D_background3_BMP_SUB	2d sub BG3 bitmap rewrite
	NNS_GFD_DST_2D_OBJECT_PLTT_SUB	2d sub OBJ palette rewrite
	NNS_GFD_DST_2D_background_PLTT_SUB	2d sub BG palette rewrite
	NNS_GFD_DST_2D_OBJECT_EXTPLTT_SUB	2d sub OBJ extended palette rewrite
	NNS_GFD_DST_2D_background_EXTPLTT_SUB	2d sub BG extended palette rewrite
	NNS_GFD_DST_2D_OBJECT_OAM_SUB	2d sub OAM rewrite
	NNS_GFD_DST_2D_OBJECT_CHAR_SUB	2d sub OBJ character rewrite

In a VRAM transfer task, the data transfer destination type shown above, the transfer destination address, the data address, and the transfer data size are stored. The actual data to be transferred is not copied, so the data should be kept in memory until the VRAM transfer manager writes it to the VRAM. The data is written to the VRAM when the user calls the `NNS_GfdDoVramTransfer()` function.

## 2.4 Executing a VRAM Transfer Task

Call the following function to write data registered to a VRAM transfer task to the VRAM.

```
void NNS_GfdDoVramTransfer(void);
```

Ordinarily, the `NNS_GfdDoVramTransfer()` function needs to be called during a V-Blank period, as that is when data can be written to VRAM. The `NNS_GfdDoVramTransfer()` function executes all VRAM transfer tasks in the order registered to the VRAM transfer manager queue. The VRAM transfer manager does not control whether all of the registered VRAM transfer tasks can be executed during a V-Blank period. The user should manage the total amount of VRAM rewrite data and register to the VRAM transfer manager only the amount that can be rewritten during a V-Blank period.

## 2.5 Obtaining the Size of the VRAM Transfer Tasks

With the VRAM transfer manager, the total size of the VRAM transfer tasks registered to the VRAM transfer manager can be obtained. Call the following function to obtain the total amount of VRAM transfer tasks.

```
u32 NNS_GfdGetVramTransferTaskTotalSize(void);
```

By using this function to obtain the total transfer amount, a determination can be made of whether a data transfer can be completed during a V-Blank.





© 2004-2005 Nintendo

The contents of this document cannot be duplicated, copied, reprinted, transferred, distributed or loaned in whole or in part without the prior approval of Nintendo.